



Referência		Passo	Largura entre Placas	Diâmetro do Rolo	PINO			PLACA		Carga de Ruptura kgf kgf		Carga de Trabalho max. kgf	Peso aprox- imado kg/m
					Diâme- tro	Compri- mento	compri- mento	Espes- sura	Altura				
ISO	ABNT	P	W	D	d	E	L	T	H	ANSI			
208A	A2040	25,40	7,95	7,95	3,96	16,60	17,80	1,50	12,00	1406	1700	311	0,42
C208A	C2040	25,40	7,95	7,95	3,96	16,60	17,80	1,50	12,00	1406	1700	311	0,50
C208AL	C2042	25,40	7,95	15,88	3,96	16,60	17,80	1,50	12,00	1406	1700	311	0,84
210A	A2050	31,75	9,53	10,16	5,08	20,70	22,20	2,03	15,00	2223	2870	525	0,73
C210	C2050	31,75	9,53	10,16	5,08	20,70	22,20	2,03	15,00	2223	2870	525	0,78
C210AL	C2052	31,75	9,53	19,05	5,08	20,70	22,20	2,03	15,00	2223	2870	525	1,27
C212A	C2060	38,10	12,7	11,91	5,94	25,90	27,70	2,42	18,00	3175	3820	671	1,12
C212AH	C2060H	38,10	12,7	11,91	5,94	29,20	31,60	3,25	18,00		4130	725	1,44
C212AL	C2062	38,10	12,7	22,23	5,94	25,90	27,70	2,42	18,00	3175	3820	671	1,61
C212AHL	C2062H	38,10	12,7	22,23	5,94	29,20	31,60	3,25	18,00		4130	725	2,07
C216A	C2080	50,80	15,88	15,88	7,92	32,70	36,50	3,25	24,00	5670	6315	1146	2,08
C216AH	C2080H	50,80	15,88	15,88	7,92	36,20	39,40	4,00	24,00		7140	1255	2,54
C216AL	C2082	50,80	15,88	28,58	7,92	32,70	36,50	3,25	24,00	5670	6315	1146	3,12
C216AHL	C2082H	50,80	15,88	28,58	7,92	36,20	39,40	4,00	24,00		7140	1295	3,58
C220AH	C2100H			19,05								2611	3,56
C220AHL	C2102H	63,50	19,05	39,67	9,53	43,60	46,90	4,80	30,00		11460	2611	5,38
C224AH	C2120H			22,23									5,26
C224AHL	C2122H	76,20	25,22	44,45	11,10	53,50	57,50	5,60	35,70		16,090	2815	8,26